HD 6/11-4M ST

A stand-alone pump unit for simple stationary and space-saving wall-mounted operation. A 3-point support on the back enables vertical or horizontal mounting.














Order no.

1.524-939.0

- Robust 4-pole low-speed AC motor
- Save time and energy: EASY!Force high-pressure gun and EASY!Lock quick-release fasteners
- Automatic pressure relief and up to 20 percent higher energy efficiency

Technical data		
EAN code		4054278504940
Current type	Ph / V / Hz	1 / 100 / 50
Flow Rate	l/h	600
Water feed temperature	°C	60
Operating pressure	/ MPa	110 / 11
Max. Pressure	bar / MPa	165 / 16.5
Power rating	kW	2.9
Power cable	m	5
Water feed		3/4"
Colour		anthracite
Weight (with accessories)	kg	25
Weight incl. packaging	kg	27.5
Dimensions (L × W × H)	mm	290 × 300 × 565

E	quipment
P	ressure switch control
	Included in delivery.





High-quality equipment

- Automatic pressure relief for protecting the components extends their service life.
- Powerful, 2-pole, air-cooled electric motor.
- High-quality brass cylinder head.



Flexible operation

■ Designed for upright and horizontal operation.



Prepared for stationary operation

- Simple and robust 3-point attachment for wall mounting on the rear of unit.
- Space-saving, compact design.
- Integrated storage options reduce the set-up times.



























14

	Т					
		Order no.	Description			
TRIGGER GUNS						
EASY!Force Advanced	1	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.			
EASY!Force conversion kit 1 - from high-pressure hose	2	4.111-050.0	For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle.			
EASY!Force conversion kit 2 - from machine	3	4.111-051.0	Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.	t [
EASY!Force conversion kit 3 - high-pressure gun	4	4.111-052.0	Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.			
SPRAY LANCES						
Rotating spray lances						
LED nozzle light	5	2.680-002.0	Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.			
Spray lance, 250 mm, rotatable	6	4.112-027.0	Spray lance, 250 mm, rotatable, ergonomic			
Spray lance, 400 mm, rotatable	7	4.112-024.0	Spray lance, 400 mm, rotatable, ergonomic			
Spray lance, 600 mm, rotatable	8	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.			
Spray lance, 840 mm, rotatable	9	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.			
Spray lance, 1050 mm, rotatable	10	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.			
Spray lance, 1550 mm, rotatable	11	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.			
Spray lance, 2050 mm, rotatable	12	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.			
Spray lance extender, 1000 mm	13	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.			
Double lance				Ė		
Double lance, 960 mm	14	2.112-016.0	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).			

 $[\]blacksquare$ Included in delivery. \qed Available accessories.























		Order no.	Description		
SPRAY LANCES					
Angular spray lance		1			
WC and gutter lance	15	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	[
Flexible spray lance				Ļ	
Flexible lance, 1050 mm	16	4.112-035.0	1050 mm flexible lance with variable bend from 20° to 140° , ideal for cleaning difficult to reach areas, e.g. gutters.	[
High pressure articulated joint	17	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.		
Gutter cleaner					
Gutter cleaning lance	18	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.		
Undercarriage spray lance					
Underbody lance	19	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.		
Additional handle					
Additional handle for EASY!Lock spray lances	20	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.		
ROTARY NOZZLES (DIRT BLASTERS)					
Dirt Blaster, small					
Dirt blaster, small, 045	21	4.114-021.0	Up to 50% higher cleaning and area performance than its predecessor: with the new performance dirt blaster (nozzle size 045), power losses have been minimised and the spray quality maximised.		
Dirt blaster, large					
Dirt blaster, large, 045	22	4.114-042.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	e [
MULTIPLE-JET NOZZLES					
Triple nozzles				ļ,	
Triple nozzle, 033	23	4.117-028.0			
Triple nozzle, 045	24	4.117-036.0	injector, the low-pressure flat stream is useful for cleaning agent suction and application.		
Angle vario nozzle 0°-90°		•		Ė	
Angled Vario nozzle, 050	25	4.113-007.0	Variable angle nozzle for spray angle adjustment from 0° to 90° . For easy adjustment to all kinds of soiling and surfaces.	- [
KÄRCHER POWER NOZZLE					
HP nozzie spray angle 0°				Ī	
Power nozzle 0°, 045	26	2.113-033.0	High-pressure nozzle with powerful jet for extremely stubborn dirt.	[
Power nozzie spray angle 15°				_	
Power nozzle 15°, 045	27	2.113-046.0	Fan jet nozzle with 15° spray angle suitable for stubborn dirt.	1	
Power nozzle spray angle 25°		1		۲	
				1	

















	_			
		Order no.	Description	
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 40°				
Power Nozzle 40°, 045	29	2.113-053.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	
NOZZLE UNION / SPACER				
Nozzle union				
Nozzle screws	30	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles	
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 10 m, ID 10, 220 bar, 2 × EASY!Lock	31	6.110-041.0		
High-pressure hose, 10 m, ID 6, 250 bar,	32	6.110-034.0	10 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating AVS trigger gun	
2 × EASY!Lock	33	6.110-035.0	connector and manual coupling. Further data: DN 6/155°C/250 bar.	
High-pressure hose, 10 m, ID 6, 300 bar, 2 × EASY!Lock	34	6.110-056.0	With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22×1.5 with anti-kink protection. NW $6/155^{\circ}$ C/300 bar	, 🗆
High-pressure hose, 10 m, ID 8, 315 bar, 2 × EASY!Lock	35	6.110-031.0	10 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating TR22 trigger gur connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	1 🗆
High-pressure hose, 15 m, ID 8, 315 bar, 2 × EASY!Lock	36	6.110-030.0	15 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	
High-pressure hose, 20 m, ID 8, 315 bar, 2 × EASY!Lock	37	6.110-032.0	20 m high-pressure hose (M 22×1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	
High-pressure hose, 30 m, ID 8, 315 bar, 2 × EASY!Lock	38	6.110-014.0	With rotary coupling, 2 × M 22 × 1.5	
High-pressure hose, 15 m, ID 10, 220 bar, 2 × EASY!Lock	39	6.110-042.0	15 m high-pressure hose M 22 \times 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155 $^{\circ}$ C/220 bar.	
High-pressure hose, 20 m, ID 10, 220 bar, 2 × EASY!Lock	40	6.110-043.0	with union on both sides, M 22 × 1.5 with anti-kink protection. NW 10/155°C/220 bar	
High-pressure hose, 25 m, ID 10, 220 bar, 2 × EASY!Lock	41	6.110-044.0		
High-pressure hose, 40 m, ID 10, 220 bar, 2 × EASY!Lock	42	6.110-045.0		

 \blacksquare Included in delivery. \qed Available accessories.

























				_
		Order no.	Description	
HIGH-PRESSURE HOSES		<u>'</u>		
Standard with unions on both sides				
High-pressure hose, 15 m, ID 12, 210 bar, 2 × EASY!Lock	43	6.110-059.0	High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22×1.5 with anti-kink protection.	[
High-pressure hose, 40 m, ID 12, 210 bar, 2 × EASY!Lock	44	6.110-060.0		[
Longlife 400 with unions on both sides				Ť
High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, 2 × EASY!Lock	45	6.110-024.0	1.5 m high-pressure hose (DN 8, M 22×1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22×1.5).	[
High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, $1 \times EASY!Lock / 1 \times M22 \times 1.5$	46	6.110-069.0	High-pressure hose (ID 8) with double steel reinforcement, 1.5 m long, suitable for up to 400 bar pressure. Connectors: M 22 × 1.5, quick and convenient EASY!Lock hand screw connection.	[
High-pressure hose Longlife, 10 m, ID 8, 400 bar, 2 × EASY!Lock	47	6.110-038.0	Durable, 10 m long high-pressure hose (ID 8) with double steel reinforcement and EASY!Lock hand screw connection at both ends and ANTI!Twist. Approved for 400 bar pressure.	[
High-pressure hose Longlife, 30 m, ID 8, 400 bar, 2 × EASY!Lock	48	6.110-023.0	With rotary coupling, 2 \times M 22 \times 1.5	[
High-pressure hose Longlife, 20 m, ID 8, 400 bar, 2 × EASY!Lock	49	6.110-027.0	with rotary coupling, 2 \times M 22 \times 1.5	[
High-pressure hose Longlife, 15 m, ID 8, 400 bar, 2 × EASY!Lock	50	6.110-029.0	With rotary coupling, 2 × M 22 × 1.5	
Food industry version with unions on both sid	es			
High-pressure hose food grade, 10 m, ID 8, 250 bar, 2 × EASY!Lock	51	6.110-051.0	10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22×1.5 with anti-kink sleeve.	[
High-pressure hose food grade, 20 m, ID 8, 250 bar, 2 × EASY!Lock	52	6.110-052.0	20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22×1.5 , with kink protection. NW 8/155°C/250 bar.	[
Longlife food industry version with unions on	both s	ides		
High-pressure hose food grade Longlife, 10 m, ID 8, 400 bar, 2 \times EASY!Lock	53	6.110-053.0	With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends.	[
High-pressure hose food grade Longlife, 20 m, ID 8, 400 bar, 2 × EASY!Lock	54	6.110-054.0	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)	[
PIPE CLEANING				
Pipe cleaning hose, ID 6				
Hose assembly TR pipe cleaning DN6 14MPa	55	6.110-108.0		[
	56	6.110-109.0		[
Available accessories		1		

[☐] Available accessories.



















	_			_
		Order no.	Description	
PIPE CLEANING				
Pipe cleaning hose, ID 6				
Hose assembly TR pipe cleaning DN6 14MPa	57	6.110-110.0		
Hose assembly TR pipe cleaning DN6 max.2	58	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, DN 6, 20 m, 220 bar	59	6.110-008.0	$20\ m$ flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R $1/8$ nozzle).	
Hose assembly TR pipe cleaning DN6 max.2	60	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Hose assembly TR pipe cleaning DN6 14MPa	61	6.110-048.0	10 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R $1/8$ nozzle).	
Pipe cleaning hose	62	6.110-049.0	20 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning hose, DN 6, 30 m	63	6.110-050.0	30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	
Pipe cleaning nozzle		l		
Dirt blaster pipe cleaning D21/060	64	4.765-002.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted	
Dirt blaster pipe cleaning D30/060	65	4.765-005.0	jets ensure the necessary forward movement, as well as convenient handling.	
Pipe cleaning nozzle	66	5.763-015.0	16 mm pipe cleaning nozzle with internal thread. Various jet directions for	
	67	5.763-016.0	environmentally-friendly cleaning of blocked drains and pipes.	
	68	5.763-017.0	30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	
Rotating pipe cleaning nozzle	69	6.415-428.0	Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	
FLOOR AND HARD SURFACE CLEANER		·		
Hard Surface Cleaner FRV 30				
FRV 30	70	2.111-010.0	Surface cleaner with integrated waste water pick-up	

 $[\]hfill \square$ Available accessories.

























				_
		Order no.	Description	
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
Add-on kit rubber lip	71	2.642-910.0	For smooth floors indoors. The squeegee increases the suction performance of the FRV 30 and minimises the amount of water remaining. This means the floor is dry in just a few minutes.	
Extension hose 5 m	72	4.440-939.0	5m extension hose for FRV 30. Connection sleeve included.	
Add-on kit hose attachment	73	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	
Add-on kit dirt trap	74	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	
Hard surface cleaner FR 30		'		
FR 30 Surface Cleaner	75	2.111-011.0	Up to 10 times greater area coverage compared with the conventional high pressure jet.	
Hard surface cleaner FR 30 ME		•		
FR 30 ME surface cleaner	76	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Machine-specific nozzle kit for FR		•		
Nozzle kit for FR, 500 l/h - 650 l/h	77	2.640-401.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).	
Hard surface cleaner FRV 30 Me				
FRV 30 Me Surface Cleaner	78	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	
Extension hose FRV 30 Me and FRV 50 Me	79	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	
FOAM SYSTEMS				
Cup foam lance				
Cup foam lance Advanced 1, 400 l/h - 600 l/h	80	4.112-063.0		
Cup foam lance DUO Advanced 1, 400 l/h - 600 l/h	81	4.112-067.0		
Cup foam lance Basic 1, 350 l/h - 600 l/h	82	4.112-053.0	For high-pressure cleaners with a flow rate of 350-600 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.	
1-litre cleaning agent container for cup foam lance basic	83	5.071-414.0		
1-litre cleaning agent container for cup foam lance advanced	84	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	

[☐] Available accessories.



























FOAM SYSTEMS		Order no.	Description	
Inno Foam Set				
Inno foam kit with detergent injector	85	2.112-000.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	
Easy Foam Set		L		Ť
Easy Foam Set with RM injector	86	2.112-010.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	
Nozzle kits for Inno/Easy Foam Set				
Nozzle kit 055 z. Inno/Easy Set 500 - 600 l/h	87	2.111-009.0	Optimal adaptation to different machine outputs for economic use.	
Foam nozzle mounting kit		•		
Foam nozzle kit	88	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	
MIXERS AND INJECTORS		·		Ė
HP detergent injector				
Detergent injector for high and low pressure (without nozzles)	89	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Detergent injector for high pressure	90	4.637-033.0	Cleaning agent dosage at high pressure 3 - 5 %	
Stainless steel injector kit for HD 6/15C	91	6.645-758.0	Ideal for the HD 6/15 C high-pressure cleaner, the stainless steel injector ensures precise cleaning agent and foam dosage. With suction hose and vacuum filter.	
Machine-specific nozzle kit with order no. 3.63	7-170)		
Nozzle insert trapezoidal thread HD-GER.	92	4.769-005.0	For HD 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union	
Nozzle insert with order no. 3.637-001				Ė
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	93	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated 1100 l/h or more	94	4.769-006.0	For low pressure with machines above 1.100 l/h	T
QUICK CONNECT				Ť
Quick-fitting pipe union coupler trapezo	95	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	
Quick-fitting pipe union plug nipple tra	96	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22×1.5 external thread.	
DRUM AND TANK CLEANING				Ť
Add-on kit mud sucker	97	2.641-798.0		
OTHER HP ACCESSORIES				ľ
Starting current limiter	98	2.637-495.0	Reduces starting current in single-phase supply and protects line fuse.	
□ Available accessories		1		_

[☐] Available accessories.





























		Order no.	Description	
OTHER HP ACCESSORIES				
Add-on kit coin acceptor	99	2.644-029.0	Coin remote control with electronic coin acceptor for connecting a high-pressure cleaner as a pre-wash device. Please have the power outlet and cable provided on site.	
Jet gun	100	2.869-067.0	Short set-up time, easy transport, instant switch off - the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	
DICHTUNGEN FÜR TR-GEWINDE				
Spare part set seals TR	101	2.880-001.0		
COUPLING PARTS				T
Rotary coupling				
Rotary coupling	102	4.111-021.0	Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector Easy!Lock. With grip protection.	[
Connector	,			
Nozzle connector/screw connector	103	4.111-022.0	Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1 \times M$ 22 \times 1.5 and $1 \times M$ 18 \times 1.5.	
Short spray unit	104	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.	t [
Adapter EASY!Lock				
Adapter 1 M22AG-TR22AG	105	4.111-029.0	Adapter 1 to connect the old hose with the new hose	
Adapter 2 M22IG-TR22AG	106	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	[
Adapter 3 M22IG-TR22AG	107	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter M22 - Swivel	108	4.111-032.0	M22 × 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	
Adapter 5 TR22IG-M22AG	109	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	[
Adapter 6 TR22IG-M22AG	110	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	[
Adapter 7 M18IG-TR20AG	111	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	[
Adapter 8 TR20IG-M18AG	112	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	[

[☐] Available accessories.



























		Order no.	Description			
COUPLING PARTS				t		
Adapter EASY!Lock						
Coupler -2xM22x1,5	113	4.111-037.0	Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \ M \ 22 \times 1.5 \ m$.			
ADAPTER for replacement TR22IG-M22AG Er	114	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection			
HOSE REELS						
Hose reel add-on kit						
Hose reel attachment kit for HD middle class, 15 m	115	2.110-024.0	Hose reel attachment kit for high-pressure middle class			
Automatic, self-winding hose reels						
Automatic plastic hose reel incl. high-pressure hose, 15 $\ensuremath{\mathrm{m}}$	116	2.639-257.0				
Automatic hose reel, powder-coated steel / plastic, 20 m	117	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.			
Automatic stainless steel / synthetic material hose drum, 20 m	118	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.			
Automatic hose reel, coated, 20 m	119	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.			
Hose reel, automatic, basalt grey-coated, 20 m	120	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.			
Automatic hose reel, stainless steel, includes swivel holder, 20 m	121	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.			
Automatic stainless steel hose reel, 40 m	122	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).			
Powder-coated swivel holder	123	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.			
Stainless steel swivel holder	124	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.			
FACADE AND SOLAR PANEL CLEANING						
Brushes						
Drive for roller brush 500	125	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.			
Splash guard for roller brush 500	126	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.			
□ Available accessories						

[☐] Available accessories.

























	Order no.	Description	
127	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.	
128	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.	
129	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.	
130	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	
131	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.	
132	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	
133	6.368-092.0	iSolar 400 brush for water flow rate of 700-1,000 l/h. The water-driven disc brush with a width of 400 mm cleans small to medium-sized photovoltaic systems. Also perfect for use on elevated systems.	
134	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	
135	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.	
136	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix. Telescopic thanks to quick-release fastenings. Up to 7 m reach.	
137	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	
138	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	
139	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	
140	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	
	128 129 130 131 132 133 134 135 136 137 138	127 4.762-623.0 128 4.762-624.0 129 4.762-625.0 130 6.960-133.0 131 6.960-134.0 132 6.960-135.0 133 6.368-092.0 134 4.580-097.0 135 4.762-609.0 136 4.762-610.0 137 4.762-611.0 138 4.762-612.0 139 4.762-613.0	 4.762-623.0 Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive. 128 4.762-624.0 Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system. 129 4.762-625.0 Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system. 130 6.960-133.0 Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher. 131 6.960-134.0 Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher. 132 6.960-135.0 For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems. 133 6.368-092.0 Isolar 400 brush for water flow rate of 700-1,000 l/h. The water-driven disc brush with a width of 400 mm cleans small to medium-sized photovoltaic systems. Also perfect for use on elevated systems. 134 4.580-097.0 TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes. 135 4.762-600.0 Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix. Telescopic thanks to quick-release fastenings. Up to 7 m reach. 136 4.762-610.0 Multifunctional uses fasteners for simple retraction and extension thanks to quick-release fasteners. Multifunctional use. Simple retraction and extension thanks to quick-release fasteners. Multifunctional use for cleaning facades, windows or solar pan

 $[\]hfill\square$ Available accessories.





















		Order no.	Description	
FACADE AND SOLAR PANEL CLEANING		1		
Wasserenthärtung				
WS 50	141	6.368-463.0	The mobile WS 50 water softening unit prevents lime residue on clean surfaces. A special ion-exchange resin removes the dissolved limescale from the water.	
WS 100	142	6.368-464.0	The mobile WS 100 water softening unit prevents lime residue on clean surfaces. A special ion-exchange resin removes the dissolved limescale from the water.	
WS Regenerator	143	6.368-465.0	With the WS Regenerator regeneration system, the softening cartridges of the water softening unit: WS 50 and WS 100 can be backflushed and regenerated at the push of a button.	s [
Hoses		•		
Hose solar	144	6.392-978.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
	145	6.392-977.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
	146	6.392-976.0	High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.	
Attachment kits and adapters				
Case sheet steel	147	6.988-152.0	Certified personal security system for rooftop work. Contents: Travelling fall arrestor with shock absorber and 15 m kernmantle rope, harness, anchoring sling and sheet steel case.	
WET BLASTING ATTACHMENT				
Wet blasting attachment (without nozzle)				
Wet blasting attachment with flow control (without nozzles)	148	4.115-000.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	149	4.115-006.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	
Nozzle pack for wet blasting attachment				
Nozzle pack TR wet jet set 0045	150	2.112-022.0	Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.115-000.0 4.115-006.0.	
Boron carbide nozzle				
Boron carbide nozzle, for machines as of 1000 l/h	151	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	
ADD-ON KITS				
HP stationary attachment kit				
	450	2.637-736.0		
Add-on kit float	152	2.037-730.0		
	152	2.637-736.0		
Add-on kit float	152	2.037-730.0		
Add-on kit float WATER CONNECTION		6.388-461.0	with hose liner	

[☐] Available accessories.























		Order no.	Description	
WATER CONNECTION	1		•	t
Geka coupling				
With hose nozzle, R 1"	155	6.388-465.0	with hose barb	
With female thread, R 3/4"	156	6.388-473.0	with female thread	
Suction filter		l .		
Water filter	157	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 μn mesh, R 3/4" and R 1" connection, without non-return valve	n [
Suction filter with check valve	158	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	Г
Fine-mesh water filter				Ė
Add-on kit water filter universal	159	2.637-020.0		
Fine-mesh water filter, 100 μm, R 3/4"	160	2.637-691.0	Fine-mesh water filter, 100 µm, max. temperature 60°C. Protects the high-pressure cleaner from dirt particles contained in the water. Transparent filter cup. Water flow rate up to 1200 l/h. Connector 3/4".	
Fine-mesh water filter with adapter	161	4.730-102.0	Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter 1".	r,
WASHING BRUSHES				Ť
Push-on washing brush				
Push-on wash brush, M 18 × 1.5	162	4.113-001.0	Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 × 1.6.	
Rotating washing brush		•		
Rotating wash brush for < 800 l/h machines, nylon bristles	163	4.113-004.0	The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60° C. (M 18×1.5 , replaceable brush insert).	
Rotating wash brush for < 800 l/h machines, natural bristles	164	4.113-003.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60° C, M 18×1.5 (replaceable brush insert).	
DRUM AND TANK CLEANING				
Barrel and tank cleaning				
Rotary cleaner head M63E	165	6.751-061.0		
□ Available accessories.		•		

 $[\]hfill \square$ Available accessories.